

1

Reborn Everyday With Hot Water



SAFE AND RELIABLE **RACOLD WATER HEATERS** FOR EVERY HOME







Reborn Everyday With Hot Water

Racold is India's most trusted brand (as per Brand Trust Report 2016) and one of the largest provider of water heating solutions for over 60 years in India. It is fully owned subsidiary of Ariston Group-Italy, the world leaders in the water and environmental heating solutions. Ever since its inception, Racold, has been setting standards in the Indian Water Heating Industry by bringing in new technology, enhancing the aesthetics, quality, safety, durability and performance of the product.

Racold has set a new benchmark in the industry for energy efficiency standards and has the distinction of being the only brand in the water heating category to win the prestigious BEE award for the 10th time in 2020. Racold is the only brand in the water heating category to be chosen as a Super brand in 2019 & 2021.

WHY CHOOSE — RACOLD FOR — WATER HEATING?







Safety Foremost



Selected Superbrand



Always At Your Service

Delivering breakthrough innovation, quality water heating solutions and complete customer satisfaction for over 60 years.

Awarded 10 times by the Bureau of Energy Efficiency from 2010-2020. We place energy efficiency at the heart of our sustainable growth strategy and are deeply committed to energy conservation.

Racold Water Heaters have multiple measures for safety against high temperature and pressure. Equipped with features that ensure thermal stability and prevent chances of hazards, when you bring home safe and reliable Racold Water Heaters, all you have to do is turn it on and relax.

Racold is the only brand in the water heating category to be selected as a Superbrand for 2019 and 2021 after an extensive online consumer voting process. It's a testimony of our continuous efforts and deep commitment to creating products that resonates with our customers.

Our network of more than 1000 service technicians and 300 service centers across the country are always at your service, for any doubts or assistance. With our 24x7 WhatsApp Chat services and Customer Care services, it's also very easy to reach out to us.

REVOLUTIONARY FEATURES OF RACOLD



EASY WATER HEATING

Making water heating easier at every step with our smart features.

Wi-Fi CONNECT

Get ease of control anywhere and anytime with Wi-Fi connect.





SMART BATH LOGIC

Customise your bathing experience with Smart Bath Logic.

LIGHTNING FAST HEATING

High powered heating element that provides hot water instantaneously.



QUICK FUNCTION

Set maximum heating temperature with a press of a button. Override temperature settings to get hot water quickly with one-press process.

REVOLUTIONARY FEATURES OF RACOLD



TITANIUM PLUS

A strong and durable heating tank, made and coated with Titanium alloys, to withstand corrosion and pressure for a long time.



RELIABLE BUILD

Your long-term partners in water heating.

TITANIUM ENAMELED HEATING ELEMENT

For efficiency, strength, low energy consumption and longer life.



Efficient water heating in utilitarian and compact sizes.





Note: Features mentioned above are not available across entire range of products. Individual features may vary from product to product.

REVOLUTIONARY FEATURES OF RACOLD



SAFETY ASSURED

Experience the power of hot water with a complete peace of mind.

AUTO DIAGNOSIS

An advanced microprocessor that safeguards the water heater to ensure complete safety of your family.





OXYGEN DEPLETING SENSOR

Safety sensor that immediately turns-off water heating in case of oxygen depletion to prevent any potential hazard.

DOUBLE SOLENOID VALVE

Advanced feature that delivers twice the safety with two solenoid valves.



SAFETY PLUS

A thermostat, multi-function safety valves and cutout for multiple level of safety against high temperature and pressure.



SILVER-ION TECHNOLOGY

It actively stops proliferation of bacteria to provide healthy and clean bathing water.



6						
		0	mnis [™] Wi-	Fi		
Yine O		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Omnis Wi-Fi Storage 15L 25L 230 Volts AC, 50 2kW 8 Wall Mounting) Hz. Sir	ngle Phase	+ PIPES
		Dimensions (in mm)	Capacity Length/Width		25L 447	
Warranty Product	2yrs.	All models available in	Depth Black	324	386	
Heating Element Inner Tank 5-Star - 25L 4	4yrs. 7yrs.	Get ease of control an	Wi-Fi Connect ywhere and anytir	ne with	Wi-Fi Co	nnect.

1		0	mnis [™] Lu>	٢			
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Omnis Lux Storage 10L 15L 25L 230 Volts AC, 50 2kW 8 Wall Mounting) Hz. Sir	ngle Pha	se	+ PIPES
	x*x	Dimensions (in mm)	Capacity Length/Width Depth	10L 360 276	15L 360 324	25L 447 386	
Warranty Product Heating Element	2yrs. 4yrs.	All models available in	Black	Sa	ndstone		
Inner Tank 5-Star - 25L 4-St	7yrs.	Sma Combination of high-tech and Eco Function for pers		Bath Lo			

Smart control is a combination of multiple functions (Smart Bath Logic, Auto Diagnosis and Eco Function) introduced for the first time in India by Racold.

7

6		
		1
		l
		l
-		I
	Ditescold	ī
1	1.11 M	l
		1

Om	nis [™] Lux ∣	Plus	5	IN	
Model Type	Omnis Lux P l us Storage			1	+ PIPES
Capacity Power Supply	10L 15L 25L 230 Volts AC, 50	ע- כוּי	alo Pha		
Wattage (kW)	igle rita	ise			
Max. Rate Pressure (Bar) Installation Type	8 Wa ll Mounting				
	Capacity	10L	15L	25L	
Dimensions (in mm)	Length/Width	360	360	447	
	Depth	276	324	386	
All models available in	Grey				
	ver Ion Technolo proliferation of ba		nrovid	۵	

healthy and clean bathing water.

5-Star - 25L | 4-Star - 10L / 15L

Warranty Product

Heating Element Inner Tank 2yrs.

Disecos		р	Andris Un	0		IN	FREE STALLATION
andris u	IND	Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Andris Uno Storage 10L 15L 25L 230 Volts AC, 50 2kW 8 Wall Mounting) Hz. Sir	ngle Pha	ase	+ PIPES
			Capacity	10L	15L	25L	
		Dimensions (in mm)	Length/Width	360	360	447	
Warranty Product	2yrs.	All models available in	Depth O White Bo with Black		326	390 White I with Sa] Body andy Panel
Heating Element	3yrs.		Titanium Plus				
Inner Tank 5-Star - 25L 4-St	5yrs. tar - 15L / 10L	Special grade steel wit high durability and s	th Titanium Ename				k

		Ang	dris Lux F	Plus
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Andris Lux Plus Storage 10L 15L 25L 230 Volts AC, 50 2kW 8 Wall Mounting) Hz. Sin
			Capacity	10L
		Dimensions (in mm)	Length/Width	360
	***		Depth	298
Warranty Product	2yrs.	All models available in	White Boo	ly with S

Warranty	4 Annual 4
Product	2yrs.
Heating Element	3yrs.
Inner Tank	5yrs.

5-Star - 25L | 4-Star - 10L/15L

Supply le (kW) ate Pressure (Bar) htion Type	230 Volts AC, 50 2kW 8 Wa ll Mounting) Hz. Sir	igle Pha	se
	Capacity	10L	15L	25L
ions (in mm)	Length/Width	360	360	447
	Depth	298	346	410
lels available in	White Boc	ly with S	Sandy Pa	anel

Silver Ion Technology It actively stops proliferation of bacteria to provide healthy and clean bathing water.

		A	ndris Sliı	n		FREE INSTALLATION
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Andris Slim** Storage 20L 30L 230 Volts AC, 5 2.5kW 8 Horizontal Wall		2	+ PIPES
Warranty		Dimensions (in mm)	Capacity Length Width Depth	20L 700 280 302	30L 754 335 340	
Product Heating Element	2yrs. 3yrs.	All models available in	O White Bo	dy with	Black Pa	nel
Inner Tank 4-Star - 20L	5yrs. . / 30L	Compact and uti	Space Saving litarian design for	urban ba	ath space	es.

**Star label obtained as per BEE guidelines considering 15 Ltr and 25 Ltr capacities for 20 Ltr and 30 Ltr products respectively.

FREE INSTALLATI + PIPES



	Ρ	latinum F	Plus		
	Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Platinum Plus Storage 50L 100L 230 Volts AC, 5 3kW 8 Vertical Wall Mc		ngle Phas	e + PIPES
		Capacity Length	50L 613	100L 993	
	Dimensions (in mm)	Width Depth	493 499	493 499	
2yrs. 3yrs.	All models available in	White			
7yrs.	New elegant and e	design with larg compact design wi technology and st	th rare o		on

5-Star - 50L / 100L

Warranty Product Heating Element Inner Tank

		P	latinum I	Eco		FREE INSTALLATION
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Platinum Eco Storage 50L 70L 230 Volts AC, 5 3kW 8 Vertical Wall Mo Capacit	ounting 50L	- 70L	+ PIPES
Warranty		Dimensions (in mm)	Length Width Depth	560 470 485	760 470 485	
roduct	2yrs.	All models available in	White			
leating Element	3yrs.					
nner Tank 4-Star - 50L	7yrs. / 70L	3 The high power 3kW l	3%** Faster Heat neating element er in no time.		ou get hot	water

10

		C	DR DI)	٢			
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	2kW 8	25L 35L AC, 50 Hz 'all Mounti	5	nase	+ PIPES
00	***	Dimensions (in mm)	Capacity Length Width	10L (v/h) 442/450 290/320	562/570	25L (v/h) 513/831 367/320	655/65
Product	2yrs.		Depth	290/320		367/320	
Heating Element Inner Tank	2yrs. 5yrs.	All models available in		ite with y Domes		lvory wit Sandy De	
5-Star (All Vertic Star - 15L / 25L & 3 (All Horizontal)	3-Star 10L / 35L	Special grade steel wit high durability and su		namel Coa			

		C	DR Swif	t	F	
		Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	50 Hz. Single f Aounting / Hori	Phase rizontal Wall Mountin		
Warranty	***	Dimensions (in mm)	Capacity Length Width Depth	6L (v/h) 394/394 290/290 290/290	10L (v/h) 442/450 290/320 290/320	
Product	2yrs.	All models available in		with Grey Dom		
Heating Element Inner Tank	2yrs. 5yrs.			with Giey Don		

MICRO STORAGE WATER HEATER RANGE



Pronto	Stylo / No	eo /	DN#				
Model Type Capacity Power Supply Wattage (kW) Max. Rate Pressure (Bar) Installation Type	Pronto Stylo / Neo / DN Instant Storage 1L 3L 6L 230 Volts AC, 50 Hz. Single Phase 3kW (1/3/6 L) 4.5kW (1/3 L) 6.5 Vertical Wall Mounting						
	Capacity	1L	3L	6L			
	Length	281	335	428			
Dimensions (in mm)	Width	175	209	270			
	Depth	172	205	253			
All models available in	White		vory				
High powere	ster Heating Elem ed heating element	that pr	ovides				

Warranty	×××××
Product	2yrs.

Heating Element	2	yrs.
Inner Tank	5	yrs.

5-Star - 6L

#Pronto Neo and Sty	lo have a varian	t in 3 Litre 3kW	with duronox	passivation in tank.

ONLINE INSTANTANEOUS WATER HEATER RANGE



	Aures	Pro			
Model	Aures Pro	24kW	+ PIPES		
Туре	Online Inst	antaneou	s		
Power Supply	415 Volts /	AC, 50 Hz	. 3 Phase		
Wattage/Step Power (kW)	24				
Max. Rate Pressure (Bar)	10				
Ampere	34.7 @ 4				
Max. Working Temp.	50°C				
Wire Thickness	400V 6Sq.mm 5 core				
Dimensions (in mm)	Length	356			
Dimensions (in mm)	Width	526			
	Depth	138			
All models available in	Blac	k			
Co With the new digita	onsistent W control, enjo		rupted hot v	vater	

Warranty Product 2yrs.

Warranty Product

		Aures Multi
	Model Type Power Supply Wattage/Step Power (kW) Max. Rate Pressure (Bar) Ampere Max. Working Temp. Wire Thickness Dimensions (in mm)	Aures Multi 5.5 kW Online Instantaneous 230 Volts AC, 50 Hz. Single Phase 5.5 kW / 2.2 kW + 3.3 kW 8 23.9 @ 230V 50°C 230V 4 Sq.mm 3 core Length 178 Width 304 Depth 98
	All models available in	White
2yrs.	High powere	htning Fast Heating of heating element that provides water instantaneously.

INSTANTANEOUS GAS WATER HEATER RANGE

NEW ()	ODS-eco+					
	Model	LPG				
ODS-eco+	Туре	Instantaneous				
64%	Capacity	6 LPM				
0 mm	Power Supply	3V DC				
应	Heat Input (kW)	12kW				
•••	Max. Rate Pressure (Bar)	8				
	Installation Type	Vertical Wall Mounting				
	Dimensions (in mm)	Length 440				
		Width 300				
		Depth 133				
	All models available in	White				
Warranty	Slock display	Digital Display panel for temperature reading.				
Product 2yrs.	Sieek uisplay	r parter for temperature reading.				



	o <mark>bs-</mark> e	CO			
Model Type Capacity Power Supply Heat Input (kW) Max. Rate Pressure (Bar) Installation Type	LPG PNG Instantaneous 6 LPM 3V DC 12kW 8 Vertical Wall Mounting				
Dimensions (in mm)	Length Width Depth	440 300 133			
All models available in	- Whi	te			
ODS (O To ensure ventilation an	xygen Depl d to avoid ar				

Warranty	
Product	2yrs.

INSTANTANEOUS GAS WATER HEATER RANGE

۲			eco	C		
		Model	LPG PNG			
eco		Туре	Instantane	ous		
617		Capacity	6 LPM			
022		Power Supply	3V DC			
应		Heat Input (kW)	12kW			
•••		Max. Rate Pressure (Bar)	8			
@·		Installation Type	Vertical W	ertical Wall Mounting		
		Dimensions (in mm)	Length	440		
	To a laboration of the laborat	Dimensions (in miny	Width	300		
TOWNS PROMINE.			Depth	133		
		All models available in	Wh	iite		
Warranty		Do Advanced safety feature wi	uble Solen ith two soler		to deliver double saf	
Product	2yrs.		comp <mark>l</mark> ete pea			

DOMESTIC SOLAR WATER HEATER

			C)mega N	eo			
		C	Model Type Capacity Outer Body Max. Rate Pressure (Bar) Safety Valve	Omega Neo Solar 100 LPD 200 LPD 250 LPD Precoated Sheet 6 Italian- 4 in 1 Multifunctional Safety Valve			ve	
				Capacity	100	200	250	
				Base Length	2400/2200	2400/2200	2400/2200	
				Base Width	1400	2500	2500	
		4	Dimensions (in mm)	Height	1685/1965	1730/2010	1730/2010	
				Tank Length	953	1376	1659	
			All models available in	🕒 Body W	/hite with b l a	ack domes	-	
	Warranty			Enameled Coat g on the inner ta		orrision		
	Tank	5yrs.		Enameled Coating on the inner tank to resist corrision from hard water for longer life.				

- mananty	
Tank	5yrs.
Collector	7yrs.
Accessory	1vr

Omega Max 8								
		Model Type Capacity Outer Body Max. Rate Pressure (Bar) Safety Valve	Omega Max 8 Solar 100 LPD 200 LPD 250 LPD 300 LPD 500 LPD Zinc Aluminium Sheet 100 to 300L – 8 bar & 500L - 4.5 bar Italian- 4 in 1 Multifunctional Safety Valve					
			Capacity Base Length	100 2400/2200	200	250	300	500
			Base Width	1316	2400/2200	2400/2200	3520	4620
and the second second		Dimensions (in mm)	Height	1625/1900	1625/1900	1625/1900	1725/2000	1725/2000
	29-199		Tank Length	1055	1830	2200	1660	2850
		All models available in	Во	dy Zn finish	with blac	k domes		
Warranty		High pressure	Max Pro withstandir		(up to 8	oar)		
Tank	5yrs.	makes it sui						
Collector	7yrs.							
Accessory	1yr.							

DOMESTIC SOLAR WATER HEATER

		Alpha Plus						
		Model Type Capacity No. of Tubes Tube Length Outer Body	Alpha Plus Solar 100 LPD 150 LPD 200 LPD 250 LPD 10 15 20 25 30 1800 mm Zinc Aluminium Sheet			LPD 3	300 LPI	
			Capacity	100	150	200	250	300
			Base Length	1965	1965	1965	1965	1965
			Base Width	812	1212	1612	2012	2412
		Dimensions (in mm)	Height	1150	1150	1150	1150	1150
			Tank Length	1008	1448	1888	2328	2768
		All models available in	Body Zr	n finish	with b	lack dc	omes	
Warranty		INOX Specially treated inner container ensures durability						
Tank	5yrs.	and re	sistance against	corrosio	on.			

Tank	5yrs.
Accessory	1 yr.
Tube	No Warranty.

Tube

No Warranty.

				Alpha P	ro			Alpha Pro						
			Model Type Capacity No, of Tubes Tube Length Outer Body	Alpha Pro Solar 100 LPD 150 LPD 200 LPD 250 LPD 300 I 10 15 20 25 30 1800 mm Zinc Aluminium Sheet					300 LP					
		A.		Capacity	100	150	200	250	300					
				Base Length	1965	1965	1965	1965	5 1965					
				Base Width	812	1212	1612	2012	2412					
			Dimensions (in mm)	Height	1150	1150	1150	1150) 1150					
				Tank Length	1197	1597	2097	2647	7 3047					
			All models available in	Body Zi	n finish	with k	olack d	omes						
Warranty			A unique float valve only o	Smart Float		elimina	tes lon	a air ve	ents					
Tank	5yrs.		to ensure safe usag											
Accessory	1yr.													

DOMESTIC HEAT PUMP WATER HEATER

NEW		Domestic Heat Pump				
		Model	Domestic Heat Pump			
		Product Configuration	Split			
1		Capacity	300 L			
		СоР	4.25			
		Heating Element (kW)	1 & 1.5			
1		Max. Rate Pressure (Bar)	8			
		Refrigerant	R134a			
		Noise Level (DB)	52			
			Capacity 300 L			
فيتعطيه بأعلا	-	Dimensions (in mm	Height 1491			
			Width 650			
		All models available in	White			
Warranty		70% Energy Savings**				
Compressor and inner tank	5yrs.	It uses electricity only to move heat from one place to another and not to generate heat, using 70% less electricity compared to conventional water				
Product	2yrs.		heating solutions.			

Heat pump water heaters have a COP (Co-efficient of performance) of 4.25, meaning that the energy produced in the form of hot water is 4.25 times more than that is consumed.

In comparison it with electric water heater the annual saving is ~₹10,000/-

^Savings are calculated @ ₹10 per unit, subject to internal lab test conditions.

		Domestic Heat Pump						
		ModelDomestic Heat PumpProduct ConfigurationSplitCapacity150 L & 200 LCoP3.8Heating Element (kW)1.8Max. Rate Pressure (Bar)8RefrigerantR134aNoise Level (DB)52						
		Dimensions (in mm)	Capacity Height Width	150 L 1486 495	200 L 1894 510			
		All models available in	🔵 wł	nite				
Warranty Compressor and inner tank Product	5yrs. 2yrs.	70% Energy Savings** It uses electricity only to move heat from one place to another and not to generate heat, using 70% less electricity compared to conventional water heating solutions.						

Heat pump water heaters have a COP (Co-efficient of performance) of 3.8, meaning that the energy produced in the form of hot water is 3.8 times more than that is consumed.

In comparison it with electric water heater the annual saving is ~₹10,000/-

^Savings are calculated @ ₹10 per unit, subject to internal lab test conditions.

COMMERCIAL SOLAR WATER HEATER

End-to-end technologically advanced hot water solutions for all types of commercial and hybrid applications. We have successful implementations across Residential, Hospitality, Medical & Healthcare, Educational Institutes and Industrial Sectors. Applications range from hot water for bathing, laundry, swimming pool, medical equipment, cleaning, industrial cleaning and much more.



COMMERCIAL HEAT PUMP

Our heat pumps water heating solutions save upto 70% electricity compared to conventional water heating solutions Commercial Heat Pump Water Heaters are available from 125L per hour(65kW) to 1000L per hour (44kW) output capacities.



In comparison it with electric water heater the annual saving is ~₹10,000/-*Subject to Internal Lab Test Conditions

CHOOSE THE BEST WATER HEATER

PROI	OUCT COMPARISON	STORAGE					
		Omnis Wi-fi	Omnis Lux	Omnis Lux Plus			
Benefits	Key Features	Ĩ.					
	Double Level Thermostat	~	~	✓			
_	Safety Valve	MFV	MFV	MFV			
Safety	Auto Diagnosis	~	~	 ✓ 			
	Anti Scalding	~	~	✓			
	Titanium Enamel HE	~	~	~			
Durability	Titanium Plus Coating	~	~	✓			
	LED Temp. Indicator	~	~	✓			
	Shower Ready	~	~	✓			
	IOT Enabled Wi-Fi	~					
	Usage Scheduler	~	~	✓			
	Power Consumption Indicator	~					
Convenience	Remote Plus Control (By App)	~					
	Quick Function		1	✓			
	Eco Function	×	×	✓			
	Smart Bath Logic	×	×	×			
	Temp. Regulation Knob	4	×	×			
	Colour Options						
Aesthetics	Body Finish	Matt	Matt	Matt			
	Design Type	Square	Square	Square			
_	Capacity (Ltr.)	15/25	10/15/25	10/15/25			
Range	Power (kW)	2	2	2			
	Length	360/447	360/360/447	360/360/447			
Dimensions	Width	360/447	360/360/447	360/360/447			
(in mm)	Depth	324/386	276/324/386	276/324/386			
	Product	2	2	2			
Warranty*	Heating Element	4	4	4			
(in years)	Tank	7	7	7			
	STAR Rating	5 Star - 25Ltr 4 Star - 15Ltr	5 Star - 25Ltr 4 Star - 15Ltr 4 Star - 10Ltr	5 Star-25Ltr 4 Star-15Ltr 4 Star-10Ltr			
Deufe	Max. Operating Pressure (Bar)	8	8	8			
Performance	Flexo / Smart Mix Technology	~	~	✓			
	Silver Ion Technology			✓			

FROM RACOLD'S LATEST RANGE

STORAGE							
Andris Uno	Andris Lux Plus	CDR DIx Vertical	CDR Dlx Horizontal				
Ō	0	<u> </u>	=====				
✓	✓	√	✓				
MFV	MFV	MFV	MFV				
Copper HE	✓	Copper HE	Copper HE				
✓	✓	✓	\checkmark				
Heating Indicator	Heating Indicator	Heating Indicator	Heating Indicator				
×	~	✓	✓				
✓	√						
Glossy	Glossy	Glossy	Glossy				
Square	Square	Cylindrical	Cylindrical				
10/15/25	10/15/25	10/15/25/35	10/15/25/35				
2	2	2	2				
360/360/447	360/360/447	442/562/513/655	450/570/831/655				
360/360/447	360/360/447	290/290/367/367	320/320/320/367				
278/326/390	298/346/410	290/290/367/367	320/320/320/367				
2	2	2	2				
3	3	2	2				
5	5	5	5				
5 Star-25Ltr 4 Star-15Ltr 4 Star-10Ltr	5 Star-25Ltr 4 Star-15Ltr 4 Star-10Ltr	5 Star	4 Star - 15/25Ltr 3 Star - 10/35Ltr				
8	8	8	8				
×	✓	✓	✓				
	✓						

CHOOSE THE BEST WATER HEATER

PROI	OUCT COMPARISON	STORAGE					
		CDR Swift - Vertical	CDR Swift - Horizontal	Platinum Plus			
Benefits	Key Features						
	Double Level Thermostat	~	✓	✓			
	Safety Valve	MFV	MFV	MFV			
Safety	Auto Diagnosis						
	Anti Scalding						
Dung kilita	Titanium Enamel HE	Copper HE	Copper HE	Copper HE			
Durability	Titanium Plus Coating	~	✓	✓			
	LED Temp Indicator	Heating Indicator	Heating Indicator	Heating Indicator			
	Shower Ready	~	 ✓ 	✓			
	IOT Enabled Wi-Fi						
	Usage Scheduler						
	Power Consumption Indicator						
Convenience	Remote Plus Control (By App)						
	Quick Function						
	Eco Function						
	Smart Bath Logic						
	Temp. Regulation Knob			\checkmark			
	Colour Options						
Aesthetics	Body Finish	Glossy	Glossy	Glossy			
	Design Type	Cylindrical	Cylindrical	Prismatic			
_	Capacity (Ltr.)	6/10	6/10	50/100			
Range	Power (kW)	3	3	3			
	Length	394/442	394/450	613/993			
Dimensions	Width	290/290	290/320	493/493			
(in mm)	Depth	290/290	290/320	499/499			
	Product	2	2	2			
Warranty*	Heating Element	2	2	3			
(in years)	Tank	5	5	7			
	STAR Rating	5 Star	4 Star	5 Star			
Porformance	Max Operating Pressure (Bar)	8	8	8			
Performance	Flexo / Smart Mix Technology	~	~	✓			
	Silver lon Technology						

FROM RACOLD'S LATEST RANGE

STORAGE	MICRO S	SLIM STORAGE	
Platinum Eco	Pronto Stylo / DN [#]	Pronto Neo / DN [#]	Andris Slim
✓	✓	✓	✓
MFV	PRV	PRV	MFV
Copper HE	Copper HE	Copper HE	Copper HE
✓	×	✓	×
Heating Indicator	Heating Indicator	Heating Indicator	Heating Indicator
✓	×	✓	~
Glossy	Glossy	Glossy	Glossy
Cylindrical	Prismatic	Prismatic	Horizontal Slim
50/70	1/3/6	1/3/6	20/30**
3	3/4.5*	3/4.5*	2.5
560/760	281/335/428	281/335/428	700/754
470/470	175/209/270	175/209/270	280/335
485/485	172/205/253	172/205/253	302/340
2	2	2	2
3	2	2	3
7	5	5	5
4 Star	5 Star (6Ltr)	5 Star (6Ltr)	4 Star
8	6.5	6.5	8
 ✓	 ✓		 ✓
	*4.5kW in only for 1/3 ltr.		*Star label obtained as per BEE guidelines
	*Pronto Neo and Stylo have a variant in 3L	itre 3kW with duronox passivation in tank.	**Star label obtained as per BEE guidelines considering 15Ltr and 25Ltr capacities for 20Ltr and 30Ltr products respectively.



Reborn Everyday With Hot Water





©73628 88999 | 🕓 1860-425-2288

MARKETED BY: ARISTON THERMO INDIA PRIVATE LIMITED

1"Floor, Office No.103, Mayfair Tower, Wakdewadi, Shivaji Nagar, Pune 411005, Maharashtra, India.

www.racold.com **f in (b)**

Customer Care Details

Email: customer.care@racold.com | Customer Care No.: 1860 425 2288 / 8600 25 6000. Address: Same as marketed by.

Disclaimer:

- 'Racold' brand is a registered trademark of Ariston Thermo Group.
- · Any dispute shall be subject to the exclusive jurisdiction of Pune Courts.
- Always use genuine Racold spare parts and connecting pipes.
- Always get your installation done by authorized Racold Service center only.
- Star rating obtained as per BEE guideline.
- Star label obtained as per BEE guidelines considering 15 Ltr and 25 Ltr capacities for 20 Ltr and 30 Ltr products respectively.
- The images are for representative purposes and the actual product may vary.
- Specifications are subject to change without prior notice.
- ^Savings are calculated @ ₹10 per unit, subject to internal lab test conditions.
- Subject to internal lab test conditions.